

WAC 173-490-020 Definitions. The definitions of terms contained in chapter 173-400 WAC are by this reference incorporated into this chapter. Unless a different meaning is clearly required by context, the following words and phrases, as used in this chapter, shall have the following meanings:

(1) "Bottom loading" means the filling of a tank through a line entering the bottom of the tank.

(2) "Bulk gasoline plant" means a gasoline storage and transfer facility that receives more than ninety percent of its annual gasoline throughput by transport tank, and reloads gasoline into transport tanks.

(3) "Class II hardboard paneling finish" means finishes which meet the specifications of Voluntary Product Standard PS-59-73 as approved by the American National Standards Institute.

(4) "Closed refinery system" means a system that will process or dispose of those VOCs collected from another system. The mass quantity of collected VOCs emitted to the ambient air from the closed refinery system shall not exceed that required for a disposal system.

(5) "Condensate" means hydrocarbon liquid separated from a gas stream which condenses due to changes in the temperature or pressure and remains liquid at standard conditions.

(6) "Condenser" means a device for cooling a gas stream to a temperature where specific VOCs become liquid and are removed.

(7) "Control system" means one or more control devices, including condensers, that are designed and operated to reduce the quantity of VOCs emitted to the atmosphere.

(8) "Crude oil" means a naturally occurring mixture which consists of hydrocarbons and sulfur, nitrogen or oxygen derivatives of hydrocarbons which is a liquid at standard conditions.

(9) "Cutback asphalt" means an asphalt that has been blended with petroleum distillates to reduce the viscosity for ease of handling and lower application temperature. An inverted emulsified asphalt shall be considered a cutback asphalt when the continuous phase of the emulsion is a cutback asphalt.

(10) "Disposal system" means a process or device that reduces the mass quantity of the VOC that would have been emitted to the ambient air by at least ninety percent prior to their actual emission.

(11) "Dry cleaning facility" means a facility engaged in the cleaning of fabrics in an essentially nonaqueous solvent by means of one or more washes in solvent, extraction of excess solvent by spinning, and drying by tumbling in an airstream. The facility includes, but is not limited to, any washer, dryer, filter and purification system(s), waste disposal system(s), holding tank(s), pump(s) and attendant piping and valve(s).

(12) "External floating roof" means a storage vessel cover in an open top tank consisting of a double deck or pontoon single deck which rests upon and is supported by the liquid being contained and is equipped with a closure seal or seals to close the space between the roof edge and tank wall.

(13) "Flexographic printing" means the application of words, designs and pictures to a substrate by means of a roll printing technique in which the pattern to be applied is raised above the printing roll and the image carrier is made of rubber or other elastomeric materials.

(14) "Gasoline" means a petroleum distillate which is a liquid at standard conditions and has a true vapor pressure greater than 200 mm

of Hg (4 psia) at 20°C, and is used as a fuel for internal combustion engines.

(15) "Gasoline dispensing facility" means any site dispensing gasoline into motor vehicle fuel tanks from stationary storage tanks.

(16) "Gasoline loading terminal" means a gasoline transfer facility that receives more than ten percent of its annual gasoline throughput solely or in combination by pipeline, ship or barge, and loads gasoline into transport tanks.

(17) "Hardboard" means a panel manufactured primarily from inter-felted lignocellulosic fibers which are consolidated under heat and pressure in a hot press.

(18) "Hardwood plywood" means plywood whose surface layer is a veneer of hardwood.

(19) "Lease custody transfer" means the transfer of produced crude oil or condensate, after processing or treating in the producing operations, from storage tanks or automatic transfer facilities to pipelines or any other forms of transportation.

(20) "Liquid-mounted seal" means a primary seal mounted in continuous contact with the liquid between the tank wall and the floating roof.

(21) "Liquid service" means equipment that processes, transfers or contains a VOC or VOCs in the liquid phase.

(22) "Low organic solvent coating" refers to coatings which contain less organic solvent than the conventional coatings used by the industry. Low organic solvent coatings include water-borne, higher solids, electrodeposition and powder coatings.

(23) "Natural finish hardwood plywood panels" means panels whose original grain pattern is enhanced by essentially transparent finishes frequently supplemented by fillers and toners.

(24) "Packaging rotogravure printing" means rotogravure printing upon paper, paper board, metal foil, plastic film, and other substrates, which are, in subsequent operations, formed into packaging products and labels for articles to be sold.

(25) "Petroleum liquids" means crude oil, condensate, and any finished or intermediate products manufactured or extracted in a petroleum refinery.

(26) "Petroleum refinery" means a facility engaged in producing gasoline, aromatics, kerosene, distillate fuel oils, residual fuel oils, lubricants, asphalt, or other products by distilling crude oils or redistilling, cracking, extracting or reforming unfinished petroleum derivatives. Not included are facilities re-refining used motor oils or waste chemicals, processing finished petroleum products, separating blended products, or air blowing asphalt.

(27) "Prime coat" means the first of two or more films of coating applied in an operation.

(28) "Printed interior panels" means panels whose grain or natural surface is obscured by fillers and basecoats upon which a simulated grain or decorative pattern is printed.

(29) "Proper attachment fittings" means hardware for the attachment of gasoline transfer or vapor collection lines that meet or exceed industrial standards or specifications and the standards of other agencies or institutions responsible for safety and health.

(30) "Publication rotogravure printing" means rotogravure printing upon paper which is subsequently formed into books, magazines, catalogues, brochures, directories, newspaper supplements, and other types of printed materials.

(31) "Refinery unit" means a set of components that are a part of a basic process operation, such as distillation, hydrotreating, cracking or reforming of hydrocarbons.

(32) "Roll printing" means the application of words, designs, and pictures to a substrate usually by means of a series of hard rubber or steel rolls each with only partial coverage.

(33) "Rotogravure printing" means the application of words, designs, and pictures to a substrate by means of a roll printing technique which involves intaglio or recessed image areas in the form of cells.

(34) "Single coat" means only one film of coating is applied to the metal substrate.

(35) "Submerged fill line" means a pipe, tube, fitting or other hardware for loading liquids into a tank with either a discharge opening flush with the tank bottom; or with a discharge opening below the lowest normal operating drawoff level or that level determined by a liquid depth two and one half times the fill line diameter when measured in the main portion of the tank, but not in sumps or similar protrusions.

(36) "Submerged loading" means the filling of a tank with a submerged fill line descending nearly to the bottom.

(37) "Suitable closure or cover" means a door, hatch, cover, lid, pipe cap, pipe blind, valve or similar device that prevents the accidental spilling or emitting of VOC. Pressure relief valves, aspirator vents or other devices specifically required for safety and fire protection are not included.

(38) "Thin particleboard" means a manufactured board one-quarter inch or less in thickness made of individual wood particles which have been coated with a binder and formed into flat sheets by pressure.

(39) "Tileboard" means paneling that has a colored waterproof surface coating.

(40) "Topcoat" means the final film or series of films of coating applied in a two-coat (or more) operation.

(41) "Transport tank" means a container used for shipping gasoline on land.

(42) "True vapor pressure" means the equilibrium partial pressure of a petroleum liquid as determined with methods described in American Petroleum Institute Bulletin 2517, 1980.

(43) "Unit turnaround" means the procedure of shutting down, repairing, inspecting, and restarting a unit.

(44) "Valves not externally regulated" means valves that have no external controls, such as in-line check valves.

(45) "Vapor collection system" means a closed system to conduct vapors displaced from a tank being filled into the tank being emptied, a vapor holding tank, or a vapor control system.

(46) "Vapor control system" means a system designed and operated to reduce or limit the emission of VOCs, or to recover the VOCs to prevent their emission into the ambient air.

(47) "Vapor-mounted seal" means a primary seal mounted so there is an annular vapor space underneath the seal. The annular vapor space is bounded by the bottom of the primary seal, the tank wall, the liquid surface, and the floating roof.

(48) "Volatile organic compound (VOC)" means any organic compound which participates in atmospheric photochemical reactions; that is, any organic compound other than those which the administrator designates as having negligible photochemical reactivity. VOC may be measured by a reference method, an equivalent method, an alternative method or

by procedures specified under 40 C.F.R. Part 60. A reference method, an equivalent method, or an alternative method, however, may also measure nonreactive organic compounds. In such cases, an owner or operator may exclude the nonreactive organic compounds when determining compliance with a standard.

(49) "Waxy, heavy pour crude oil" means a crude oil with a pour point of 50°F or higher as determined by the American Society for Testing and Materials Standard D97-66, "Test for Pour Point of Petroleum Oils."

[Statutory Authority: Chapter 70.94 RCW. WSR 91-05-064 (Order 90-06), § 173-490-020, filed 2/19/91, effective 3/22/91. Statutory Authority: Chapters 70.94 and 43.21A RCW. WSR 82-16-021 (Order DE 82-22), § 173-490-020, filed 7/27/82. Statutory Authority: RCW 70.94.331, 70.94.510, and 70.94.785. WSR 81-03-003 (Order DE 80-54), § 173-490-020, filed 1/8/81. Statutory Authority: RCW 70.94.331 and 70.94.395. WSR 80-11-062 (Order DE 80-18), § 173-490-020, filed 8/20/80. Statutory Authority: RCW 43.21A.080 and 70.94.331. WSR 79-06-011 (Order DE 78-23), § 173-490-020, filed 5/8/79.]