WAC 51-50-0506 Section 506—Building area. Table 506.2 Allowable Area Factor (At = NS, S1, S13R, S13D or SM, as applicable) In Square Feet^{a,b}

Octopaney Classification See Footnotes A B A B A B A B A B A B A B A B A B A			Type of Construction											
NS	Occupancy Classification	See Footnotes	Tyl	pe I	Type II				Type IV			Т		oe V
SI			A	В	A	В	A	В	A	В	С	HT	A	В
SM	A-1	NS	UL	UL	15,500	8,500	14,000	8,500	45,000	30,000	18,750	15,000	11,500	5,500
A-2		S1	UL	UL	62,000	34,000	56,000	34,000	180,000	120,000	75,000	60,000	46,000	22,000
SI		SM	UL	UL	46,500	25,500	42,000	25,500	135,000	90,000	56,250	45,000	34,500	16,500
SM	A-2	NS		UL	15,500	9,500	14,000	9,500	45,000	30,000	18,750	15,000	11,500	6,000
A-3				UL	62,000	38,000	56,000	38,000	180,000	120,000	75,000	60,000	46,000	24,000
S1		SM	UL	UL	46,500	28,500	42,000	28,500	135,000	90,000	56,250	45,000	34,500	18,000
SM	A-3	NS		UL	15,500	9,500	14,000	9,500	45,000	30,000		15,000	11,500	6,000
A-4		S1		UL	62,000	38,000	56,000	38,000	180,000	120,000	75,000	60,000	46,000	24,000
S1		SM	UL	UL	46,500	28,500	42,000	28,500	135,000	90,000	56,250	45,000	34,500	18,000
SM	A-4	NS	UL	UL	15,500	9,500	14,000	9,500	45,000	30,000	18,750	15,000	11,500	6,000
$\begin{array}{c c c c c c c c c c c c c c c c c c c $		S1	UL	UL	62,000	38,000	56,000	38,000	180,000	120,000	75,000	60,000	46,000	24,000
SI		SM	UL	UL	46,500	28,500	42,000	28,500	135,000	90,000	56,250	45,000	34,500	18,000
SM	A-5	NS	UL	UL	UL	UL	UL	UL	UL	UL	UL	UL	UL	UL
B		S1												
$\begin{array}{c ccccccccccccccccccccccccccccccccccc$		SM												
SM	В	NS	UL	UL	37,500	23,000	28,500	19,000	108,000	72,000	45,000	36,000	18,000	9,000
E		S1	UL	UL	150,000	92,000	114,000	76,000	432,000	288,000	180,000	144,000	72,000	36,000
S1		SM	UL	UL	112,500	69,000	85,500	57,000	324,000	216,000	135,000	108,000	54,000	27,000
$ \begin{array}{ c c c c c c c c c c c c c c c c c c c$	Е	NS	UL	UL	26,500	14,500	23,500	14,500	76,500	51,000	31,875	25,500	18,500	9,500
F-1 NS UL UL 100,000 15,500 19,000 12,000 100,500 67,000 41,875 33,500 14,000 8,500 S1 UL UL 100,000 62,000 76,000 48,000 402,000 268,000 167,500 134,000 56,000 34,000 SM UL UL 75,000 46,500 57,000 36,000 301,500 201,000 125,625 100,500 42,000 25,500 S1 UL UL 37,500 23,000 28,500 18,000 151,500 101,000 63,125 50,500 21,000 13,000 SM UL UL 150,000 92,000 114,000 72,000 606,000 404,000 252,500 202,000 84,000 52,000 SM UL UL 112,500 69,000 85,500 54,000 454,500 303,000 189,375 151,500 63,000 39,000 S1		S1	UL	UL	106,000	58,000	94,000	58,000	306,000	204,000	127,500	102,000	74,000	38,000
S1		SM	UL	UL	79,500	43,500	70,500	43,500	229,500	153,000	95,625	76,500	55,500	28,500
SM	F-1	NS	UL	UL	25,000	15,500	19,000	12,000	100,500	67,000	41,875	33,500	14,000	8,500
F-2 NS UL UL 37,500 23,000 28,500 18,000 151,500 101,000 63,125 50,500 21,000 13,000 S1 UL UL 150,000 92,000 114,000 72,000 606,000 404,000 252,500 202,000 84,000 52,000 SM UL UL 112,500 69,000 85,500 54,000 454,500 303,000 189,375 151,500 63,000 39,000 S1 NS° 21,000 16,500 11,000 7,000 9.500 7,000 10,500 10,500 10,000 10,500 7,500 NP S1 S1 SN SM UL OL SNS° 21,000 16,500 11,000 7,000 9.500 7,000 10,500 10,500 10,000 10,500 7,500 3,000 S1 S1 SM UL 60,000 26,500 14,000 17,500 13,000 25,500 25,500 25,500 25,500 10,000 5,000 S1 S1 SM SS° UL 60,000 26,500 14,000 17,500 13,000 25,500 25,500 25,500 25,500 10,000 5,000 S1 S1 S1 S1 SN S° UL 60,000 26,500 14,000 17,500 13,000 25,500 25,500 25,500 25,500 10,000 5,000 S1		S1	UL	UL	100,000	62,000	76,000	48,000	402,000	268,000	167,500	134,000	56,000	34,000
S1		SM	UL	UL	75,000	46,500	57,000	36,000	301,500	201,000	125,625	100,500	42,000	25,500
SM	F-2	NS	UL	UL	37,500	23,000	28,500	18,000	151,500	101,000	63,125	50,500	21,000	13,000
H-1 NS ^c 21,000 16,500 11,000 7,000 9.500 7,000 10,500 10,000 10,500 7,500 NP H-2 NS ^c 21,000 16,500 11,000 7,000 9.500 7,000 10,500 10,500 10,000 10,500 7,500 3,000 S1 SM		S1	UL	UL	150,000	92,000	114,000	72,000	606,000	404,000	252,500	202,000	84,000	52,000
H-2 NSc 21,000 16,500 11,000 7,000 9.500 7,000 10,500 10,500 10,500 7,500 3,000 S1 SM UL 60,000 26,500 14,000 17,500 13,000 25,500 25,500 25,500 25,500 10,000 5,000 S1		SM	UL	UL	112,500	69,000	85,500	54,000	454,500	303,000	189,375	151,500	63,000	39,000
H-2 NSc 21,000 16,500 11,000 7,000 9.500 7,000 10,500 10,000 10,500 7,500 3,000 S1 SM UL 60,000 26,500 14,000 17,500 13,000 25,500 25,500 25,500 25,500 10,000 5,000	H-1	NSc	21,000	16,500	11,000	7,000	9.500	7,000	10,500	10,500	10,000	10,500	7,500	NP
NS		S1												
NSC	H-2	NSc	21,000	16,500	11,000	7,000	9.500	7,000	10,500	10,500	10,000	10,500	7,500	3,000
H-3 NS° UL 60,000 26,500 14,000 17,500 13,000 25,500 25,500 25,500 10,000 5,000		S1												
S1 S1		SM												
S1 S1	H-3	NSc	UL	60,000	26,500	14,000	17,500	13,000	25,500	25,500	25,500	25,500	10,000	5,000
						ŕ	, and the second			, and the second	ĺ		, and the second	
H-4 NS ^{c,d} UL UL 37,500 17,500 28,500 17,500 72,000 54,000 40,500 36,000 18,000 6,500	H-4		UL	UL	37,500	17,500	28,500	17,500	72,000	54,000	40,500	36,000	18,000	6,500
S1 UL UL 150,000 70,000 114,000 70,000 288,000 216,000 162,000 144,000 72,000 26,000		S1	UL	UL	150,000	70,000	114,000	70,000	288,000	216,000	162,000	144,000	72,000	26,000
SM UL UL 112,500 52,500 85,500 52,500 216,000 162,000 121,500 108,000 54,000 19,500					112,500	52,500		52,500		162,000		108,000		·
H-5 NS ^{c,d} UL UL 37,500 23,000 28,500 19,000 72,000 54,000 40,500 36,000 18,000 9,000	H-5												18,000	
S1 UL UL 150,000 92,000 114,000 76,000 288,000 216,000 162,000 144,000 72,000 36,000			UL	UL	150,000	92,000	114,000	76,000	288,000	216,000		144,000		36,000
SM UL UL 112,500 69,000 85,500 57,000 216,000 162,000 121,500 108,000 54,000 27,000														

		Type of Construction												
Occupancy Classification	See Footnotes	Type I		Type II		Type III		Тур		e IV		Тур	e V	
		A	В	A	В	A	В	A	В	C	HT	A	В	
I-1	NS ^{d, e}	UL	55,000	19,000	10,000	16,500	10,000	54,000	36,000	18,000	18,000	10,500	4,500	
	S1	UL	220,000	76,000	40,000	66,000	40,000	216,000	144,000	72,000	72,000	42,000	18,000	
	SM	UL	165,000	57,000	30,000	49,500	30,000	162,000	108,000	54,000	54,000	31,500	13,500	
I-2	NS ^{d, f}	UL	UL	15,000	11,000	12,000	NP	36,000	24,000	12,000	12,000	9,500	NP	
	S1	UL	UL	60,000	44,000	48,000	NP	144,000	96,000	48,000	48,000	38,000	NP	
	SM	UL	UL	45,000	33,000	36,000	NP	108,000	72,000	36,000	36,000	28,500	NP	
I-3	NS ^{d, e}	UL	UL	15,000	10,000	10,500	7,500	36,000	24,000	12,000	12,000	7,500	5,000	
	S1	UL	UL	45,000	40,000	42,000	30,000	144,000	96,000	48,000	48,000	30,000	20,000	
	SM	UL	UL	45,000	30,000	31,500	22,500	108,000	72,000	36,000	36,000	22,500	15,000	
I-4	NS ^{d, g}	UL	60.500	26,500	13,000	23,500	13,000	76,500	51,000	25,500	25,500	18,500	9,000	
	S1	UL	121,000	106,000	52,000	94,000	52,000	306,000	204,000	102,000	102,000	74,000	36,000	
	SM	UL	181,500	79,500	39,000	70,500	39,000	229,500	153,000	76,500	76,500	55,500	27,000	
M	NS	UL	UL	21,500	12,500	18,500	12,500	61,500	41,000	25,625	20,500	14,000	9,000	
	S1	UL	UL	86,000	50,000	74,000	50,000	246,000	164,000	102,500	82,000	56,000	36,000	
	SM	UL	UL	64,500	37,500	55,500	37,500	184,500	123,000	76,875	61,500	42,000	27,000	
R-1 ^h	NS ^d	UL	UL	24,000	16,000	24,000	16,000	61,500	41,000	25,625	20,500	12,000	7,000	
*	S13R													
	S1	UL	UL	96,000	64,000	96,000	64,000	246,000	164,000	102,500	82,000	48,000	28,000	
	SM	UL	UL	72,000	48,000	72,000	48,000	184,500	123,000	76,875	61,500	36,000	21,000	
R-2 ^h	NSd	UL	UL	24,000	16,000	24,000	16,000	61,500	41,000	25.625	20,500	12,000	7,000	
	S13R													
	S1	UL	UL	96,000	64,000	96,000	64,000	246,000	164,000	102,500	82,000	48,000	28,000	
	SM	UL	UL	72,000	48,000	72,000	48,000	184,500	123,000	76,875	61,500	36,000	21,000	
R-3 ^h	NSd	UL	UL	UL	UL	UL	UL	UL	UL	UL	UL	UL	UL	
	S13D													
	S13R													
	S1													
	SM													
R-4 ^h	NS ^d	UL	UL	24,000	16,000	24,000	16,000	61,500	41,000	25,625	20,500	12,000	7,000	
	S13D													
	S13R													
	S1	UL	UL	96,000	64,000	96,000	64,000	246,000	164,000	102,500	82,000	48,000	28,000	
	SM	UL	UL	72,000	48,000	72,000	48,000	184,500	123,000	76,875	61,500	36,000	21,000	
S-1	NS	UL	48,000	26,000	17,500	26,000	17,500	76,500	51,000	31,875	25,500	14,000	9,000	
	S1	UL	192,000	104,000	70,000	104,000	70,000	306,000	204,000	127,500	102,000	56,000	36,000	
	SM	UL	144,000	78,000	52,500	78,000	52,500	229,500	153,000	95,625	76,500	42,000	27,000	
S-2	NS	UL	79,000	39,000	26,000	39,000	26,000	115,500	77,000	48,125	38,500	21,000	13,500	
	S1	UL	316,000	156,000	104,000	156,000	104,000	462,000	308,000	192,500	154,000	84,000	54,000	
	SM	UL	237,000	117,000	78,000	117,000	78,000	346,500	231,000	144,375	115,500	63,000	40,500	
U	NSi	UL	35,500	19,000	8,500	14,000	8,500	54,000	36,000	22,500	18,000	9,000	5,500	
	S1	UL	142,000	76,000	34,000	56,000	34,000	216,000	144,000	90,000	72,000	36,000	22,000	
	SM	UL	106,500	57,000	25,500	42,000	25,500	162,000	108,000	67,500	54,000	27,000	16,500	

For SI: 1 square foot = 0.0929 m². UL = Unlimited; NP = Not permitted; NS = Buildings not equipped throughout with an automatic sprinkler system; S1 = Buildings a maximum of one story above grade plane equipped throughout with an automatic sprinkler system installed in accordance with Section 903.3.1.1; SM = Buildings two or more stories above grade plane equipped throughout with an automatic sprinkler system installed in accordance with Section 903.3.1.1; S13R = Buildings equipped throughout with an automatic sprinkler system installed in accordance with Section 903.3.1.2; S13D = Buildings equipped throughout with an automatic sprinkler system installed in accordance with Section 903.3.1.3.

a See Chapters 4 and 5 for specific exceptions to the allowable height in this chapter.

- b See Section 903.2 for the minimum thresholds for protection by an automatic sprinkler system for specific occupancies.
- c New Group H occupancies are required to be protected by an automatic sprinkler system in accordance with Section 903.2.5.
- d The NS value is only for use in evaluation of existing building area in accordance with the International Existing Building Code.
- New Group I-1 and I-3 occupancies are required to be protected by an automatic sprinkler system in accordance with Section 903.2.6. For new Group I-1 occupancies Condition 1, see Exception 1 of Section 903.2.6.

- f New and existing Group I-2 occupancies are required to be protected by an automatic sprinkler system in accordance with Section 903.2.6 and Section 1103.5 of the *International Fire Code*.
- g For new Group I-4 occupancies, see Exceptions 2 and 3 of Section 903.2.6.
- h New Group R occupancies are required to be protected by an automatic sprinkler system in accordance with Section 903.2.8.
- ¹ The maximum allowable area for a single-story nonsprinklered Group U greenhouse is permitted to be 9,000 square feet, or the allowable area shall be permitted to comply with Table C102.1 of Appendix C.

[Statutory Authority: RCW 19.27.031 and 19.27.074. WSR 20-01-090, § 51-50-0506, filed 12/12/19, effective 7/1/20; WSR 19-02-038, § 51-50-0506, filed 12/26/18, effective 7/1/19; WSR 16-03-064, § 51-50-0506, filed 1/19/16, effective 7/1/16. Statutory Authority: RCW 19.27.031 and chapters 19.27 and 34.05 RCW. WSR 13-04-067, § 51-50-0506, filed 2/1/13, effective 7/1/13. Statutory Authority: RCW 19.27.031 and 19.27.074. WSR 10-03-097, § 51-50-0506, filed 1/20/10, effective 7/1/10. Statutory Authority: RCW 19.27.074, 19.27.020, and chapters 70.92, 19.27, and 34.05 RCW. WSR 07-01-091, § 51-50-0506, filed 12/19/06, effective 7/1/07.]