WAC 246-240-623 Records of periodic spot-checks for gamma stereotactic radiosurgery units. (1) A licensee shall retain a record of each spot-check for gamma stereotactic radiosurgery units required by WAC 246-240-384 for three years.

- (2) The record must include:
- (a) The date of the spot-check;
- (b) The manufacturer's name, model number, and serial number for the gamma stereotactic radiosurgery unit and the instrument used to measure the output of the unit;
  - (c) An assessment of timer linearity and accuracy;
  - (d) The calculated on-off error;
  - (e) A determination of trunnion centricity;
- (f) The difference between the anticipated output and the measured output;
  - (g) An assessment of source output against computer calculations;
- (h) Notations indicating the operability of radiation monitors, helmet microswitches, emergency timing circuits, emergency off buttons, electrical interlocks, source exposure indicator lights, viewing and intercom systems, timer termination, treatment table retraction mechanism, and stereotactic frames and localizing devices (trunnions); and
- (i) The name of the individual who performed the periodic spotcheck and the signature of the authorized medical physicist who reviewed the record of the spot-check.
- (3) A licensee shall retain a copy of the procedures required by WAC 246-240-384(2) until the licensee no longer possesses the gamma stereotactic radiosurgery unit.

[Statutory Authority: RCW 70.98.050. WSR 06-05-019, \$ 246-240-623, filed 2/6/06, effective 3/9/06.]