- WAC 222-24-060 Rock quarries, gravel pits, borrow pits, and spoil disposal areas. Not covered by the Surface Mine Reclamation Act of 1971 (chapter 78.44 RCW).
- \*(1) Location of pits. Except as approved by the department, rock quarries and gravel pits opened after January 1, 1975 shall be located above the 100-year flood level.
- \*(2) Location of spoil disposal areas. Except as approved by the department, spoil disposal areas shall be located:
  - (a) Above the 100-year flood level.
- (b) Where the final slope after disposal will be no steeper than  $1\ 1/2:1.$
- (c) Where practical, on areas having low potential timber productivity.
- (d) Where the risk of sediment delivery from soil erosion and/or mass soil movement is minimal.
- (e) All spoils shall be placed to allow drainage without additional water ponding.
- (f) All spoils shall be located outside of Type A and Type B Wetlands and their wetland management zones. Spoils shall not be located within the boundaries of forested wetlands without written approval of the department and unless a less environmentally damaging location is unavailable. No spoil area greater than 0.5 acre in size shall be allowed within wetlands. (See WAC 222-24-015.)
- \*(3) **Pit drainage.** During construction and use of rock quarries, gravel pits, or borrow pits, runoff water shall be either diverted onto a stable portion of the forest floor or be passed through one or more settling basins as approved by the department.
- \*(4) Rehabilitation required. All rock quarries, gravel pits, spoil disposal areas and borrow pits used after January 1, 1975 shall be reclaimed within 2 years from the time the rock or gravel source is either exhausted or abandoned.
  - \*(5) Rehabilitation standards. Where rehabilitation is required:
- (a) Remove all deleterious material that has potential for damaging the public resource, the soil productivity, or that would prevent reforestation of an otherwise plantable area.
- (b) Grade slopes to less than the angle of repose unless otherwise approved.
- (c) Reforest in accordance with chapter 222-34 WAC to the extent practical.
- (d) Seed nonforested exposed erodible soils with grass, clover or other ground cover.
- \*(6) Major spoil disposal operations. Where a spoil disposal operation involves more than 1,000 cubic yards of spoils:
- (a) The spoils shall be placed to provide drainage onto a stable portion of the forest floor without water ponding within the disposal area;
- (b) The site shall be reforested in accordance with chapter 222-34 WAC to the extent practical; and
- (c) If significant erosion of the spoils develops, the eroding areas shall be water barred and any unreforested areas shall be matted, mulched, or seeded with grass or ground cover.

[Statutory Authority: Chapter 34.05 RCW, RCW 76.09.040, [76.09.]050, [76.09.]370, 76.13.120(9). WSR 01-12-042, \$ 222-24-060, filed 5/30/01, effective 7/1/01. Statutory Authority: RCW 76.09.040, 76.09.050 and chapter 34.05 RCW. WSR 92-15-011, \$ 222-24-060, filed 7/2/92, effective 8/2/92. Statutory Authority: RCW 76.09.040. WSR 87-23-036 (Order

535), § 222-24-060, filed 11/16/87, effective 1/1/88; Order 263, § 222-24-060, filed 6/16/76.]