WAC 296-307-36851 Wiring for transformers. (1) This section applies to the installation of all transformers.

Exceptions:

- 1. Current transformers;
- 2. Dry-type transformers installed as a component part of other apparatus;
 3. Transformers that are an integral part of a high frequency or electrostatic-coating apparatus;
 4. Transformers used with Class 2 and Class 3 circuits, sign and outline lighting, electric discharge lighting, and power-limited fire-
- protective signaling circuits; and
 5. Liquid-filled or dry-type transformers used for research, development, or testing, where effective safeguard arrangements are

provided.

- The operating voltage of exposed live parts of transformer installations must be indicated by warning signs or visible markings on the equipment or structure.
- (3) Dry-type, high fire point liquid-insulated, and askarel-insulated transformers installed indoors and rated over 35kV must be in a vault.
- (4) If they present a fire hazard to employees, oil-insulated transformers installed indoors must be in a vault.
- Combustible material, combustible buildings and parts of buildings, fire escapes, and door and window openings must be safeguarded from fires that may originate in oil-insulated transformers attached or adjacent to a building or combustible material.
- (6) Transformer vaults must be constructed to contain fire and combustible liquids within the vault and to prevent unauthorized access. Locks and latches must be arranged so that a vault door can be readily opened from the inside.
- (7) Any pipe or duct system foreign to the vault installation must not enter or pass through a transformer vault.
 - (8) Materials must not be stored in transformer vaults.

Authority: RCW 49.17.010, 49.17.040, 49.17.050, [Statutory 49.17.060. WSR 20-21-091, § 296-307-36851, filed 10/20/20, effective 11/20/20. WSR 97-09-013, recodified as § 296-307-36851, filed 4/7/97, effective 4/7/97. Statutory Authority: RCW 49.17.040, [49.17.]050 and [49.17.]060. WSR 96-22-048, § 296-306A-36851, filed 10/31/96, effective 12/1/96.1