## (Effective until July 1, 2023)

## Table C403.3.2(5)-Minimum efficiency re-WAC 51-11C-403235 quirements-Gas- and oil-fired boilers.

## Table C403.3.2(5)

## Minimum Efficiency Requirements-Gas- and Oil-Fired Boilers

Equipment Type <sup>a</sup>	Subcategory or Rating Condition	Size Category (Input)	Minimum Efficiency	Test Procedure
Boilers, hot water	Gas-fired	< 300,000 Btu/h <sup>d,e</sup>	82% AFUE	10 C.F.R. Part 430
		$ \ge 300,000 \text{ Btu/h and} \\ \le 2,500,000 \text{ Btu/h}^b $	80% E <sub>t</sub>	10 C.F.R. Part 431
		> 2,500,000 Btu/h <sup>a</sup>	82% E <sub>c</sub>	
	Oil-fired <sup>c</sup>	< 300,000 Btu/h <sup>e</sup>	84% AFUE	10 C.F.R. Part 430
		$\geq$ 300,000 Btu/h and $\leq$ 2,500,000 Btu/h <sup>b</sup>	$82\% E_t$	10 C.F.R. Part 431
		> 2,500,000 Btu/h <sup>a</sup>	84% E <sub>c</sub>	
Boilers, steam	Gas-fired	< 300,000 Btu/h <sup>d</sup>	80% AFUE	10 C.F.R. Part 430
	Gas-fired - All, except natural draft	$ \begin{tabular}{l} $\geq$ 300,000 $ Btu/h and $$ $\leq$ 2,500,000 $ Btu/h^b$ \end{tabular} tabular$	79% E <sub>t</sub>	10 C.F.R. Part 431
		> 2,500,000 Btu/h <sup>a</sup>	79% E <sub>t</sub>	
	Gas-fired-natural draft	$ \begin{array}{l} \geq 300,\!000 \; Btu/h \; and \\ \leq 2,\!500,\!000 \; Btu/h^b \end{array} $	79% <i>E</i> <sub>t</sub>	
		> 2,500,000 Btu/h <sup>a</sup>	79% E <sub>t</sub>	
	Oil-fired <sup>c</sup>	< 300,000 Btu/h	82% AFUE	10 C.F.R. Part 430
		$ \begin{array}{r} \geq 300,\!000 \; Btu/h \; and \\ \leq 2,\!500,\!000 \; Btu/h^b \end{array} $	81% <i>E</i> <sub>t</sub>	10 C.F.R. Part 431
		> 2,500,000 Btu/h <sup>a</sup>	81% E <sub>t</sub>	

For SI: 1 British thermal unit per hour = 0.2931 W.

> Ec Combustion efficiency (100 percent less flue losses).

Thermal efficiency. See referenced standard document for detailed information. Et

These requirements apply to boilers with rated input of 8,000,000 Btu/h or less that are not packaged boilers and to all packaged boilers. Minimum а efficiency requirements for boilers cover all capacities of packaged boilers. Maximum capacity minimum and maximum ratings as provided for and allowed by the unit's controls.

b

Includes oil-fired (residual). с

d Boilers shall not be equipped with a constant burning ignition pilot.

A boiler not equipped with a tankless domestic water heating coil shall be equipped with an automatic means for adjusting the temperature of the water such that an incremental change in inferred heat load produces a corresponding incremental change in the temperature of the water supplied. e

[Statutory Authority: RCW 19.27A.020, 19.27A.025, 19.27A.160 and chapter 19.27 RCW. WSR 19-24-040, § 51-11C-403235, filed 11/26/19, effec-tive 7/1/20. Statutory Authority: RCW 19.27A.025, 19.27A.160, and and 19.27.074. WSR 16-03-072, § 51-11C-403235, filed 1/19/16, effective 7/1/16. Statutory Authority: RCW 19.27A.020, 19.27A.025 and chapters 19.27 and 34.05 RCW. WSR 13-04-056, § 51-11C-403235, filed 2/1/13, effective 7/1/13.]