(Effective until July 1, 2023)

WAC 51-50-1019 Section 1019—Exit access stairways and ramps.

1019.3 Occupancies other than Groups I-2 and I-3. In other than Groups I-2 and I-3 occupancies, floor openings containing exit access stairways or ramps shall be enclosed with a shaft enclosure constructed in accordance with Section 713.

EXCEPTIONS:

- 1. Exit access stairways and ramps that serve or atmospherically communicate between only two stories. Such interconnected stories shall not be open to other stories.
- 2. In Group R-1, R-2 or R-3 occupancies, exit access stairways and ramps connecting four stories or less serving and contained within an individual dwelling unit or sleeping unit or live/work unit.
- 3. Exit access stairways serving and contained within a Group R-3 congregate residence are not required to be enclosed.
- 4. Exit access stairways and ramps in buildings equipped throughout with an automatic sprinkler system in accordance with Section 903.3.1.1, where the area of the vertical opening between stories does not exceed twice the horizontal projected area of the stairway or ramp and the opening is protected by a draft curtain and closely spaced sprinklers in accordance with NFPA 13. In other than Group B and M occupancies, this provision is limited to openings that do not connect more than four stories.
- 5. Exit access stairways and ramps within an atrium complying with the provisions of Section 404.
- 6. Exit access stairways and ramps in open parking garages that serve only the parking garage.
 7. Exit access stairways and ramps serving smoke-protected or open-air assembly seating complying with the exit access travel distance requirements of Section 1029.7.
- 8. Exit access stairways and ramps between the balcony, gallery or press box and the main assembly floor in occupancies such as theaters, places of religious worship, auditoriums, and sports facilities.

[Statutory Authority: RCW 19.27.031 and 19.27.074. WSR 20-21-021, 51-50-1019, filed 10/9/20, effective 11/9/20; 51-50-1019, filed 12/12/19, effective 7/1/20; WSR 20-01-090, WSR 10-03-097, 51-50-1019, filed 1/20/10, effective 7/1/10. Statutory Authority: RCW 19.27.074, 19.27.020, and chapters 70.92, 19.27, and 34.05 RCW. WSR 07-01-091, § 51-50-1019, filed 12/19/06, effective 7/1/07.]

(Effective July 1, 2023)

WAC 51-50-1019 Section 1019—Exit access stairways and ramps.

1019.3 Occupancies other than Groups I-2 and I-3. In other than Groups I-2 and I-3 occupancies, floor openings containing exit access stairways or ramps shall be enclosed with a shaft enclosure constructed in accordance with Section 713.

EXCEPTIONS:

- 1. Exit access stairways and ramps that serve or atmospherically communicate between only two adjacent stories. Such interconnected stories shall not be open to other stories.
- 2. In Group R-1, R-2 or R-3 occupancies, exit access stairways and ramps connecting four stories or less serving and contained within an individual dwelling unit or sleeping unit or live/work unit.
- 3. Exit access stairways serving and contained within a Group R-3 congregate residence are not required to be enclosed.
- 4. Exit access stairways and ramps in buildings equipped throughout with an automatic sprinkler system in accordance with Section 903.3.1.1, where the area of the vertical opening between stories does not exceed twice the horizontal projected area of the stairway or ramp and the opening is protected by a draft curtain and closely spaced sprinklers in accordance with NFPA 13. In other than Group B and M occupancies, this provision is limited to openings that do not connect more than four stories.
- 5. Exit access stairways and ramps within an atrium complying with the provisions of Section 404.
- 6. Exit access stairways and ramps in open parking garages that serve only the parking garage.
- 7. Exit access stairways and ramps serving smoke-protected or open-air assembly seating complying with the exit access travel distance requirements of Section 1030.7.
- 8. Exit access stairways and ramps between the balcony, gallery or press box and the main assembly floor in occupancies such as theaters, places of religious worship, auditoriums, and sports facilities.
- 9. Exterior exit access stairways or ramps between occupied roofs.

```
[Statutory Authority: RCW 19.27.031 and 19.27.074. WSR 22-13-094,
51-50-1019,
              filed 6/14/22, effective
                                             7/1/23;
                                                        WSR
                                                              20-21-021,
51-50-1019, filed 10/9/20, effective 11/9/20; 51-50-1019, filed 12/12/19, effective 7/1/20;
                                                        WSR
                                                              20-01-090,
                                                        WSR
                                                              10-03-097,
51-50-1019, filed 1/20/10, effective 7/1/10. Statutory Authority: RCW
19.27.074, 19.27.020, and chapters 70.92, 19.27, and 34.05 RCW. WSR
07-01-091, § 51-50-1019, filed 12/19/06, effective 7/1/07.]
```