- WAC 296-54-535 Hand and portable powered tools. (1) Each hand and portable powered tool, including any tool provided by an employee, must be maintained in serviceable condition.
- (2) Each tool, including any tool provided by an employee, must be inspected before initial use during each workshift. The inspection must include at least the following:
- (a) Handles and guards, to ensure that they are sound and tight-fitting, (properly shaped, free of splinters and sharp edges, and in place);
  - (b) Controls, to ensure proper function;
  - (c) Chain saw chains, to ensure proper adjustment;
- (d) Chain saw mufflers, to ensure that they are operational and in place;
- (e) Chain brakes and/or nose shielding devices, to ensure that they are in place and function properly;
- (f) Heads of shock, impact-driven and driving tools, to ensure that there is no mushrooming.
- (3) Each tool must be used and maintained according to the following requirements:
- (a) Each tool is used only for purposes for which it was designed.
- (b) Any shock, impact-driven or driving tool is repaired or removed from service when the head begins to chip.
- (c) The cutting edge of each tool is sharpened according to manufacturer's specifications whenever it becomes dull during the workshift.
- (d) Each tool is stored in the provided location when not being used at a worksite.

Note: See chapter 296-807 WAC, Portable power tools, for rules on the use and maintenance of tools and other equipment not covered by this chapter.

[Statutory Authority: RCW 49.17.010, 49.17.040, 49.17.050, 49.17.060. WSR 07-03-163, § 296-54-535, filed 1/24/07, effective 4/1/07. Statutory Authority: RCW 49.17.010, [49.17].040 and [49.17].050. WSR 99-17-117, amended and recodified as § 296-54-535, filed 8/18/99, effective 12/1/99. Statutory Authority: RCW 49.17.040, [49.17].050 and [49.17].060. WSR 96-22-013, § 296-54-523, filed 10/28/96, effective 1/1/97. Statutory Authority: RCW 49.17.040, 49.17.150 and 49.17.240. WSR 79-10-081 (Order 79-14), § 296-54-523, filed 9/21/79.]