

*(Effective until July 1, 2020)*

**WAC 51-50-30020 Section 30020—Hoistway enclosures.**

**30020.4 Elevator car to accommodate ambulance stretcher.** Where elevators are provided in buildings four or more stories above, or four or more stories below, grade plane, or in any Group R-1, R-2 or I occupancy building provided with an elevator regardless of the number of stories, not fewer than one elevator shall be provided for fire department emergency access to all floors. The elevator car shall be of such a size and arrangement to accommodate an ambulance stretcher 24-inch by 84-inch (610 mm by 2,134 mm) with not less than 5-inch (127 mm) radius corners, in the horizontal, open position and shall be identified by the international symbol for emergency medical services (star of life). The symbol shall not be less than 3 inches (76 mm) in height and shall be placed inside on both sides of the hoistway door frame.

[Statutory Authority: RCW 19.27.031 and 19.27.074. WSR 16-03-064, § 51-50-30020, filed 1/19/16, effective 7/1/16.]

*(Effective July 1, 2020)*

**WAC 51-50-30020 Reserved.**

[Statutory Authority: RCW 19.27.031 and 19.27.074. WSR 20-01-090, § 51-50-30020, filed 12/12/19, effective 7/1/20; WSR 16-03-064, § 51-50-30020, filed 1/19/16, effective 7/1/16.]