

**WAC 204-50-070 Variable calibration of an ignition interlock device.** To be certified, an ignition interlock device must be capable of being preset, by only the manufacturer, at any fail level from .02 through .09 g/210L BrAC (plus or minus .005 g/210L BrAC). The actual setting of each ignition interlock device, unless otherwise mandated by the originating court, must be .025 g/210L BrAC. The capability to change this setting must be made secure, by the manufacturer.

[Statutory Authority: RCW 43.43.395, 46.37.005, and 46.04.215. WSR 12-17-153, § 204-50-070, filed 8/22/12, effective 10/1/12; WSR 10-24-074, § 204-50-070, filed 11/30/10, effective 1/1/11. Statutory Authority: RCW 46.37.005 and 46.04.215. WSR 09-18-073, § 204-50-070, filed 8/31/09, effective 10/1/09. Statutory Authority: RCW 46.61.688(2). WSR 05-17-065, § 204-50-070, filed 8/11/05, effective 9/11/05. Statutory Authority: RCW 46.04.215 and 46.37.005. WSR 99-01-156, § 204-50-070, filed 12/23/98, effective 1/1/99. Statutory Authority: 1987 c 247. WSR 88-01-020 (Order 87-05-ESR), § 204-50-070, filed 12/9/87.]