

WAC 296-869-60035 Elevating and lowering the platform. (1) You must have the operator make sure all of the following are done before each elevation of the platform:

(a) The elevating work platform is on a surface that is within the limits specified by the manufacturer;

(b) Outriggers, stabilizers, extendable axes, or other stability enhancing means are used as required by the manufacturer;

(c) Guardrails are installed and access gates or openings are closed per the manufacturer's instructions;

(d) The load and its distribution on the platform and any platform extension does not exceed the manufacturer's rated capacity for the configuration being used;

(e) There is adequate clearance from overhead obstructions;

(f) The minimum safe approach distance (MSAD) to energized power lines and parts listed in Table 6, Minimum Safe Approach Distance, is maintained;

(g) All persons on the platform are wearing fall protection devices and other safety gear if required.

(2) You must prevent rope, electric cords, hoses and similar objects from becoming entangled with the platform.

(3) You must have the operator make sure the area is clear of personnel and equipment before lowering the platform.

(4) You must remove all personnel from a platform that has been caught, snagged, or otherwise prevented from normal motion before attempting to free it using ground controls.

Note: If possible, reverse the platform controls to free a platform that is caught, snagged, or otherwise prevented from normal motion by an adjacent structure or other obstacle.

**Table 6
Minimum Safe Approach Distance**

Voltage	Minimum Safe Approach Distance
Less than 300 volts (insulated lines)	3 feet (0.9 m)
Less than 300 volts (uninsulated lines)	10 feet (3.1 m)
300 volts to 50 kv	10 feet (3.1 m)
More than 50 kv	10 feet (3.1 m) + 0.4 inches (1.0 cm) for each 1 kv over 50 kv

[Statutory Authority: RCW 49.17.010, 49.17.040, 49.17.050. WSR 15-23-086, § 296-869-60035, filed 11/17/15, effective 12/18/15. Statutory Authority: RCW 49.17.010, 49.17.040, 49.17.050, 49.17.060. WSR 06-19-073, § 296-869-60035, filed 9/19/06, effective 1/1/07.]