

WAC 296-150C-1100 Flame-spread limitations. (1) The interior finish of all walls and partitions must have a flame-spread rating not exceeding two hundred except as otherwise specified in this section. The flame-spread limitation does not apply to:

(a) Molding, trim, windows, doors, or series of doors four feet wide or less;

(b) Permanently attached decorative items such as pictures or accent panels constituting a maximum of ten percent of the aggregate wall surface in any room or space or more than thirty-two square feet in surface area, whichever is less.

(2) All ceiling interior finish must have a maximum flame-spread rating of two hundred, excluding molding and trim two inches wide or less.

(3) Furnace and water heater spaces must be enclosed by walls, ceiling, and doors having an interior finish with a maximum flame-spread of twenty-five.

(4) Combustible kitchen cabinet doors, countertops, exposed bottom and end panels must have a maximum flame-spread of twenty-five. Cabinet rails, stiles, mullions, and toe strips are exempted.

(5) Exposed interior finishes adjacent to the cooking range must have a flame-spread of fifty. Adjacent surfaces are the exposed vertical surfaces between the range top and the overhead cabinets or ceiling and within six horizontal inches of the cooking range.

(6) Finish surfaces of plastic bath tubs, shower units and tub or shower doors must have a flame-spread of two hundred.

[Statutory Authority: RCW 43.22.340, [43.22.]355, [43.22.]360, [43.22.]432, [43.22.]440 and [43.22.]480. WSR 96-21-146, § 296-150C-1100, filed 10/23/96, effective 11/25/96.]