

WAC 468-95-328 School crossing assembly. Pursuant to RCW 46.61.235(1), replace Option paragraphs 04 and 06 and Standard paragraph 07 in MUTCD Section 7B.12 with the following:

Option:

The In-Street Pedestrian Crossing (R1-6a) sign (see Section 2B.12 and Figure 7B-6) or the In-Street Schoolchildren Crossing (R1-6c) sign (see Figure 7B-6) may be used at unsignalized school crossings. If used at a school crossing, a 12 inch x 4 inch SCHOOL (S4-3P) plaque (see Figure 7B-6) may be mounted above the sign. The STATE LAW legend on the R1-6 series signs may be omitted.

A 12 inch reduced size in-street School (S1-1) sign (see Figure 7B-6) may be used at an unsignalized school crossing instead of the In-Street Pedestrian Crossing (R1-6a) sign or the In-Street Schoolchildren Crossing (R1-6c) sign. A 12 inch x 6 inch reduced size diagonal downward pointing arrow (W16-7P) plaque may be mounted below the reduced size in-street School (S1-1) sign.

Standard:

If an In-Street Pedestrian Crossing sign, an In-Street Schoolchildren Crossing sign, or a reduced size in-street School (S1-1) sign is placed in the roadway, the sign support shall comply with the mounting height and special mounting support requirements for In-Street Pedestrian Crossing (R1-6a) signs.

[Statutory Authority: RCW 47.36.030. WSR 11-23-101, § 468-95-328, filed 11/18/11, effective 12/19/11.]