

WAC 173-400-070 Emission standards for certain source categories. Ecology finds that the reasonable regulation of sources within certain categories requires separate standards applicable to such categories. The standards set forth in this section shall be the maximum allowable standards for emissions units within the categories listed. Except as specifically provided in this section, such emissions units shall not be required to meet the provisions of WAC 173-400-040, 173-400-050 and 173-400-060.

(1) **Wigwam and silo burners.** As of January 1, 2020, it is illegal to use a wigwam or silo burner in Washington. A wigwam or silo burner may operate until midnight December 31, 2019, provided it complies with the following:

(a) All wigwam and silo burners designed to dispose of waste wood must meet all provisions of WAC 173-400-040 (2), (3), (4), (5), (6), (7), (8), and WAC 173-400-050(4), 173-400-115, or 40 C.F.R. Part 62, Subpart III in effect on the date in WAC 173-400-025 as applicable.

(b) All wigwam and silo burners must use RACT. All emissions units shall be operated and maintained to minimize emissions. These requirements may include a controlled tangential vent overfire air system, an adequate underfire system, elimination of all unnecessary openings, a controlled feed and other modifications determined necessary by ecology or the permitting authority.

(c) It shall be unlawful to install or increase the existing use of any burner that does not meet all requirements for new sources including those requirements specified in WAC 173-400-040 and 173-400-050, except operating hours.

(d) The permit authority may establish additional requirements for wigwam and silo burners. These requirements may include, but shall not be limited to:

(i) A requirement to meet all provisions of WAC 173-400-040 and 173-400-050. Wigwam and silo burners will be considered to be in compliance if they meet the requirements contained in WAC 173-400-040(2), visible emissions.

(ii) A requirement to apply BACT.

(iii) A requirement to reduce or eliminate emissions if ecology establishes that such emissions unreasonably interfere with the use and enjoyment of the property of others or are a cause of violation of ambient air standards.

(2) **Hog fuel boilers.**

(a) Hog fuel boilers shall meet all provisions of WAC 173-400-040 and 173-400-050(1).

(b) All hog fuel boilers shall utilize RACT and shall be operated and maintained to minimize emissions.

(3) **Orchard heating.**

(a) Burning of rubber materials, asphaltic products, crankcase oil or petroleum wastes, plastic, or garbage is prohibited.

(b) This provision is in effect until the effective date of EPA's removal of the September 20, 1993, version of WAC 173-400-107 from the SIP. It is unlawful to burn any material or operate any orchard-heating device that causes a visible emission exceeding twenty percent opacity, except during the first thirty minutes after such device or material is ignited.

(c) This provision takes effect on the effective date of EPA's removal of the September 20, 1993, version of WAC 173-400-107 from the SIP. It is unlawful to burn any material or operate an orchard-heating device that causes a visible emission exceeding twenty percent opacity as specified in WAC 173-400-040(2).

(4) **Grain elevators.** Any grain elevator which is primarily classified as a materials handling operation shall meet all the provisions of WAC 173-400-040 (2), (3), (4), and (5).

(5) **Other waste wood burners.**

(a) Waste wood burners not specifically provided for in this section shall meet all applicable provisions of:

(i) WAC 173-400-040 and 173-400-050;

(ii) 40 C.F.R. Part 60, Subpart CCCC (in effect on the date in WAC 173-400-025); and

(iii) 40 C.F.R. Part 62, Subpart III (in effect on the date in WAC 173-400-025).

(b) Such waste wood burners shall utilize RACT and shall be operated and maintained to minimize emissions.

(6) **Municipal solid waste landfills constructed, reconstructed, or modified before May 30, 1991.** A municipal solid waste landfill that commenced construction prior to May 30, 1991, and has not been modified or reconstructed since May 30, 1991, must comply with the requirements in 40 C.F.R. Part 62, Subpart GGG (in effect on the date in WAC 173-400-025). A municipal solid waste landfill (MSW landfill) is an entire disposal facility in a contiguous geographical space where household waste is placed in or on the land. A MSW landfill may also receive other types of waste regulated under Subtitle D of the Federal Resource Conservation and Recovery Act including the following: Commercial solid waste, nonhazardous sludge, conditionally exempt small quantity generator waste, and industrial solid waste. Portions of an MSW landfill may be separated by access roads. A MSW landfill may be either publicly or privately owned. A MSW landfill may be a new MSW landfill, an existing MSW landfill, or a lateral expansion. All references in this subsection to 40 C.F.R. Part 60 rules mean those rules in effect on the date in WAC 173-400-025.

(a) **Applicability.** These rules apply to each MSW landfill constructed, reconstructed, or modified before May 30, 1991; and the MSW landfill accepted waste at any time since November 8, 1987 or the landfill has additional capacity for future waste deposition. (See WAC 173-400-115 for the requirements for MSW landfills constructed, reconstructed, or modified on or after May 30, 1991.) Terms in this subsection have the meaning given them in 40 C.F.R. 60.751, except that every use of the word "administrator" in the federal rules referred to in this subsection includes the "permitting authority."

(b) **Exceptions.** Any physical or operational change to an MSW landfill made solely to comply with these rules is not considered a modification or rebuilding.

(c) **Standards for MSW landfill emissions.**

(i) A MSW landfill having a design capacity less than 2.5 million megagrams or 2.5 million cubic meters must comply with the requirements of 40 C.F.R. 60.752(a) in addition to the applicable requirements specified in this section.

(ii) A MSW landfill having design capacity equal to or greater than 2.5 million megagrams and 2.5 million cubic meters must comply with the requirements of 40 C.F.R. 60.752(b) in addition to the applicable requirements specified in this section.

(d) **Recordkeeping and reporting.** A MSW landfill must follow the recordkeeping and reporting requirements in 40 C.F.R. 60.757 (submission of an initial design capacity report) and 40 C.F.R. 60.758 (recordkeeping requirements), as applicable, except as provided for under (d) (i) and (ii).

(i) The initial design capacity report for the facility is due before September 20, 2001.

(ii) The initial nonmethane organic compound (NMOC) emissions rate report is due before September 20, 2001.

(e) Test methods and procedures.

(i) A MSW landfill having a design capacity equal to or greater than 2.5 million megagrams and 2.5 million cubic meters must calculate the landfill nonmethane organic compound emission rates following the procedures listed in 40 C.F.R. 60.754, as applicable, to determine whether the rate equals or exceeds 50 megagrams per year.

(ii) Gas collection and control systems must meet the requirements in 40 C.F.R. 60.752 (b)(2)(ii) through the following procedures:

(A) The systems must follow the operational standards in 40 C.F.R. 60.753.

(B) The systems must follow the compliance provisions in 40 C.F.R. 60.755 (a)(1) through (a)(6) to determine whether the system is in compliance with 40 C.F.R. 60.752 (b)(2)(ii).

(C) The system must follow the applicable monitoring provisions in 40 C.F.R. 60.756.

(f) Conditions. Existing MSW landfills that meet the following conditions must install a gas collection and control system:

(i) The landfill accepted waste at any time since November 8, 1987, or the landfill has additional design capacity available for future waste deposition;

(ii) The landfill has design capacity greater than or equal to 2.5 million megagrams or 2.5 million cubic meters. The landfill may calculate design capacity in either megagrams or cubic meters for comparison with the exception values. Any density conversions shall be documented and submitted with the report; and

(iii) The landfill has a nonmethane organic compound (NMOC) emission rate of 50 megagrams per year or greater.

(g) Change in conditions. After the adoption date of this rule, a landfill that meets all three conditions in (e) of this subsection must comply with all the requirements of this section within thirty months of the date when the conditions were met. This change will usually occur because the NMOC emission rate equaled or exceeded the rate of 50 megagrams per year.

(h) Gas collection and control systems.

(i) Gas collection and control systems must meet the requirements in 40 C.F.R. 60.752 (b)(2)(ii).

(ii) The design plans must be prepared by a licensed professional engineer and submitted to the permitting authority within one year after the adoption date of this section.

(iii) The system must be installed within eighteen months after the submittal of the design plans.

(iv) The system must be operational within thirty months after the adoption date of this section.

(v) The emissions that are collected must be controlled in one of three ways:

(A) An open flare designed and operated according to 40 C.F.R. 60.18;

(B) A control system designed and operated to reduce NMOC by 98 percent by weight; or

(C) An enclosed combustor designed and operated to reduce the outlet NMOC concentration to 20 parts per million as hexane by volume, dry basis to three percent oxygen, or less.

(i) Air operating permit.

(i) A MSW landfill that has a design capacity less than 2.5 million megagrams or 2.5 million cubic meters on January 7, 2000, is not subject to the air operating permit regulation, unless the landfill is subject to chapter 173-401 WAC for some other reason. If the design capacity of an exempted MSW landfill subsequently increases to equal or exceed 2.5 million megagrams or 2.5 million cubic meters by a change that is not a modification or reconstruction, the landfill is subject to chapter 173-401 WAC on the date the amended design capacity report is due.

(ii) A MSW landfill that has a design capacity equal to or greater than 2.5 million megagrams or 2.5 million cubic meters on January 7, 2000, is subject to chapter 173-401 WAC beginning on the effective date of this section. (Note: Under 40 C.F.R. 62.14352(e), an applicable MSW landfill must have submitted its application so that by April 6, 2001, the permitting authority was able to determine that it was timely and complete. Under 40 C.F.R. 70.7(b), no source may operate after the time that it is required to submit a timely and complete application.)

(iii) When a MSW landfill is closed, the owner or operator is no longer subject to the requirement to maintain an operating permit for the landfill if the landfill is not subject to chapter 173-401 WAC for some other reason and if either of the following conditions are met:

(A) The landfill was never subject to the requirement for a control system under 40 C.F.R. 62.14353; or

(B) The landfill meets the conditions for control system removal specified in 40 C.F.R. 60.752 (b) (2) (v).

(7) Municipal solid waste landfills that commenced construction on or before July 17, 2014, and have not been modified or reconstructed since July 17, 2014. A municipal solid waste landfill that commenced construction on or before July 17, 2014, and has not been modified or reconstructed since July 17, 2014, must comply with the requirements in 40 C.F.R. Part 62, Subpart 000 (in effect on the date in WAC 173-400-025).

[Statutory Authority: RCW 70A.30.010. WSR 23-01-102 (Order 21-12), § 173-400-070, filed 12/19/22, effective 1/19/23. Statutory Authority: Chapter 70.94 RCW. WSR 18-17-111 (Order 15-07), § 173-400-070, filed 8/16/18, effective 9/16/18. Statutory Authority: RCW 70.94.152, 70.94.331, 70.94.860. WSR 16-12-099 (Order 16-01), § 173-400-070, filed 5/31/16, effective 7/1/16. Statutory Authority: Chapter 70.94 RCW. WSR 12-24-027 (Order 11-10), § 173-400-070, filed 11/28/12, effective 12/29/12; WSR 11-06-060 (Order 09-01), § 173-400-070, filed 3/1/11, effective 4/1/11. Statutory Authority: RCW 70.94.152. WSR 05-03-033 (Order 03-07), § 173-400-070, filed 1/10/05, effective 2/10/05. Statutory Authority: Chapter 70.94 RCW, RCW 70.94.141, [70.94.]152, [70.94.]331, [70.94.]510 and 43.21A.080. WSR 01-17-062 (Order 99-06), § 173-400-070, filed 8/15/01, effective 9/15/01. Statutory Authority: [RCW 70.94.331, 70.94.510 and chapter 70.94 RCW.] WSR 00-23-130 (Order 98-27), § 173-400-070, filed 11/22/00, effective 12/23/00. Statutory Authority: RCW 70.94.860, 70.94.510 and 70.94.331. WSR 98-15-129 (Order 98-04), § 173-400-070, filed 7/21/98, effective 8/21/98. Statutory Authority: Chapter 70.94 RCW. WSR 96-19-054 (Order 94-35), § 173-400-070, filed 9/13/96, effective 10/14/96; WSR 91-05-064 (Order 90-06), § 173-400-070, filed 2/19/91, effective 3/22/91. Statutory Authority: Chapters 43.21A and 70.94 RCW. WSR 83-09-036 (Order DE 83-13), § 173-400-070, filed 4/15/83. Statutory Authority: RCW 70.94.331. WSR 80-11-059 (Order DE 80-14), §

173-400-070, filed 8/20/80. Statutory Authority: RCW 43.21A.080 and 70.94.331. WSR 79-06-012 (Order DE 78-21), § 173-400-070, filed 5/8/79; Order DE 76-38, § 173-400-070, filed 12/21/76. Formerly WAC 18-04-070.]