

**WAC 204-50-070 Alcohol set point of an ignition interlock device.** (1) An ignition interlock device must be capable of being pre-set by the manufacturer to an alcohol set point from .020 to .070 BrAC.

(2) The alcohol set point of each ignition interlock device must be set at .020 BrAC, unless otherwise mandated by the originating court.

(3) The capability to change the set point must be made secure by the manufacturer.

(4) The manufacturer must notify the impaired driving section in writing within seven calendar days of installing an ignition interlock device with an alcohol set point other than .020 BrAC.

(5) As used in this chapter, "alcohol set point" means the BrAC level at which the ignition interlock device will prevent the operator from starting the vehicle, and once the vehicle is started, the level below which the operator must record a test.

[Statutory Authority: RCW 43.43.395, 46.37.005, and 46.04.215. WSR 22-01-068, § 204-50-070, filed 12/9/21, effective 1/9/22; WSR 12-17-153, § 204-50-070, filed 8/22/12, effective 10/1/12; WSR 10-24-074, § 204-50-070, filed 11/30/10, effective 1/1/11. Statutory Authority: RCW 46.37.005 and 46.04.215. WSR 09-18-073, § 204-50-070, filed 8/31/09, effective 10/1/09. Statutory Authority: RCW 46.61.688(2). WSR 05-17-065, § 204-50-070, filed 8/11/05, effective 9/11/05. Statutory Authority: RCW 46.04.215 and 46.37.005. WSR 99-01-156, § 204-50-070, filed 12/23/98, effective 1/1/99. Statutory Authority: 1987 c 247. WSR 88-01-020 (Order 87-05-ESR), § 204-50-070, filed 12/9/87.]