

WAC 296-96-02650 Additional required on-site documentation. (1)

Wiring diagrams.

(2) A log identifying applicable tests.

(3) Manufacturer's operational instructions that include the operation of the manual lowering device.

(4) Maintenance logs shall include the following tasks:

(a) Stair chair lifts:

(i) Platform lifts:

(A) Operating control devices;

(B) Seat, arm rests, and foot rest;

(C) Rated load and data plate; and

(D) Ride.

(ii) Machine:

(A) Enclosure;

(B) Drive machine brake;

(C) Suspension means;

(D) Disconnecting means;

(E) Numbering of equipment;

(F) Gears and bearings;

(G) Winding drum;

(H) Suspension fastenings;

(I) Slack-rope devices; and

(J) Overspeed governor.

(iii) Runway:

(A) Normal terminal stopping devices;

(B) Final terminal stopping devices;

(C) Head room;

(D) Guiding members;

(E) Construction;

(F) Clearances;

(G) Traveling cables and junction boxes;

(H) Guide rail fastenings and equipment; and

(I) Equipment exposure to weather.

(b) Inclined platform lifts:

(i) Platform:

(A) Stop switch;

(B) Operating control devices;

(C) Floor;

(D) Lighting;

(E) Emergency signal;

(F) Signs and operating device symbols;

(G) Rated load and data plates;

(H) Ride; and

(I) Arms and retractable ramps.

(ii) Machine:

(A) Enclosure;

(B) Guarding of exposed auxiliary equipment;

(C) Drive machine brake;

(D) Gears and bearings;

(E) Winding drum;

(F) Belt or chain drive;

(G) Secondary and deflector sheaves;

(H) Suspension fastenings;

(I) Slack-rope devices;

(J) Safety device;

(K) Overspeed governor;

(L) Disconnecting means;

- (M) Numbering of equipment; and
- (N) Controller.
- (iii) Runway:
 - (A) Normal terminal stopping devices;
 - (B) Final terminal stopping devices;
 - (C) Head room;
 - (D) Slack rope devices;
 - (E) Safeties and guiding members;
 - (F) Construction;
 - (G) Clearances;
 - (H) Guide rail fastenings and equipment;
 - (I) Suspension means; and
 - (J) Equipment exposure to weather.
- (c) Vertical platform lifts:
 - (i) Platform:
 - (A) Stop switch;
 - (B) Operating control devices;
 - (C) Lighting and auxiliary lighting;
 - (D) Emergency signaling device;
 - (E) Gates and retractable ramps;
 - (F) Enclosure;
 - (G) Signs and operating device symbols;
 - (H) Rated load and data plate; and
 - (I) Ride.
 - (ii) Machine:
 - (A) Enclosure;
 - (B) Drive machine brake;
 - (C) Gears and bearings;
 - (D) Winding drum;
 - (E) Belt or chain drive machine;
 - (F) Secondary or deflector sheaves;
 - (G) Suspension fastenings;
 - (H) Slack rope device;
 - (I) Overspeed governors;
 - (J) Hydraulic power unit;
 - (K) Control valves; and
 - (L) Hydraulic cylinders and supply piping.
 - (iii) Runways:
 - (A) Normal terminal stopping device;
 - (B) Final terminal stopping device;
 - (C) Head room;
 - (D) Slack rope device;
 - (E) Safeties and guiding members;
 - (F) Construction;
 - (G) Clearances;
 - (H) Traveling cables;
 - (I) Door and gate equipment;
 - (J) Suspension fastenings;
 - (K) Suspension means; and
 - (L) Equipment exposure to weather.
 - (iv) Outside runway:
 - (A) Doors and gates;
 - (B) Door locking devices; and
 - (C) Enclosure.

[Statutory Authority: Chapter 70.87 RCW. WSR 21-18-096, § 296-96-02650, filed 8/31/21, effective 10/1/21.]