

RCW 46.37.200 Stop lamps and electric turn signals displayed.

(1) Any vehicle may be equipped and when required under this chapter shall be equipped with a stop lamp or lamps on the rear of the vehicle which shall display a red or amber light, or any shade of color between red and amber, visible from a distance of not less than one hundred feet and on any vehicle manufactured or assembled after January 1, 1964, three hundred feet to the rear in normal sunlight, and which shall be actuated upon application of a service brake, and which may but need not be incorporated with one or more other rear lamps. However, for commercial motor vehicles defined in RCW 46.32.005, stop lamps must be red.

(2) Any vehicle may be equipped and when required under RCW 46.37.070(2) shall be equipped with electric turn signals which shall indicate an intention to turn by flashing lights showing to the front and rear of a vehicle or on a combination of vehicles on the side of the vehicle or combination toward which the turn is to be made. The lamps showing to the front shall be mounted on the same level and as widely spaced laterally as practicable and, when signaling, shall emit amber light: PROVIDED, That on any vehicle manufactured prior to January 1, 1969, the lamps showing to the front may emit white or amber light, or any shade of light between white and amber. The lamp showing to the rear shall be mounted on the same level and as widely spaced laterally as practicable, and, when signaling, shall emit a red or amber light, or any shade of color between red and amber. Turn signal lamps shall be visible from a distance of not less than five hundred feet to the front and rear in normal sunlight. Turn signal lamps may, but need not be, incorporated in other lamps on the vehicle.

(3) Any vehicle may be equipped and when required under this chapter shall be equipped with a center high-mounted stop lamp mounted on the center line of the rear of the vehicle. These stop lamps shall display a red light visible from a distance of not less than three hundred feet to the rear in normal sunlight, and shall be actuated upon application of a service brake, and may not be incorporated with any other rear lamps. [2019 c 321 § 2; 2006 c 306 § 3; 1977 ex.s. c 355 § 17; 1963 c 154 § 15; 1961 c 12 § 46.37.200. Prior: 1955 c 269 § 20; prior: 1953 c 248 § 2, part; 1947 c 267 § 4, part; 1937 c 189 § 23, part; Rem. Supp. 1947 § 6360-23, part; RCW 46.40.090, part; 1929 c 178 § 1, part; 1927 c 309 § 15, part; RRS § 6362-15.]

Severability—1977 ex.s. c 355: See note following RCW 46.37.010.

Effective date—1963 c 154: See note following RCW 46.37.010.