

WAC 204-10-060 Reflectors. (1) On motor vehicles, reflex reflectors must be securely mounted on a rigid part of the vehicle with the plane of the lens perpendicular to the roadway and parallel to the rear axle. Side reflex reflectors must be mounted with the lens face perpendicular to the roadway and parallel to the rear wheels.

(2) On bicycles, the reflectors must be securely mounted and of a type conforming to 16 C.F.R. Part 1512.

(3) On motorized foot scooters, a red reflector on the rear that is visible from a distance of five hundred feet when directly in front of lawful upper beams of headlamps on a motor vehicle. It shall also be equipped with reflective material and of sufficient size and reflectivity to be visible from both sides at a distance of five hundred feet.

[Statutory Authority: RCW 46.37.005, 46.37.320, and 46.20.500. WSR 21-01-054, § 204-10-060, filed 12/9/20, effective 1/9/21. Statutory Authority: RCW 46.37.005 and 46.37.320. WSR 08-19-079, § 204-10-060, filed 9/16/08, effective 10/17/08. Statutory Authority: RCW 46.37.005, 46.37.194, 46.37.280, 46.37.310, 46.37.320 and 46.37.380. WSR 81-18-008 (Order 81-08-02), § 204-10-060, filed 8/21/81.]