

(Effective until March 16, 2024)

WAC 51-50-481009 Section 1009—Plumbing.

1009.1 Increased demand. Where the occupancy of an existing building or part of an existing building is changed such that the new occupancy is subject to increased or different plumbing fixture requirements or to increased water supply requirements in accordance with the Uniform Plumbing Code, the new occupancy shall comply with the intent of the respective Uniform Plumbing Code provisions.

1009.2 Food-handling occupancies. If the new occupancy is a food-handling establishment, all existing sanitary waste lines above the food or drink preparation or storage areas shall be panned or otherwise protected to prevent leaking pipes or condensation on pipes from contaminating food or drink. New drainage lines shall not be installed above such areas and shall be protected in accordance with the Uniform Plumbing Code.

1009.3 Interceptor required. If the new occupancy will produce grease or oil-laden wastes, interceptors shall be provided as required in the Uniform Plumbing Code.

1009.5 Group I-2. If the occupancy group is changed to Group I-2, the plumbing system shall comply with the applicable requirements of the Uniform Plumbing Code.

[Statutory Authority: RCW 19.27.031 and 19.27.074. WSR 20-21-021, § 51-50-481009, filed 10/9/20, effective 11/9/20.]

(Effective March 16, 2024)

WAC 51-50-481009 Section 1009—Plumbing.

1009.1 Increased demand. Where the occupancy of an existing building or part of an existing building is changed such that the new occupancy is subject to increased or different plumbing fixture requirements or to increased water supply requirements in accordance with the Uniform Plumbing Code, the new occupancy shall comply with the intent of the respective Uniform Plumbing Code provisions.

EXCEPTION: Only where the occupant load of the story is increased by more than 20 percent, plumbing fixtures for the story shall be provided in quantities specified in Chapter 29 of the *International Building Code*, based on the increased occupant load.

1009.2 Food-handling occupancies. If the new occupancy is a food-handling establishment, all existing sanitary waste lines above the food or drink preparation or storage areas shall be panned or otherwise protected to prevent leaking pipes or condensation on pipes from contaminating food or drink. New drainage lines shall not be installed above such areas and shall be protected in accordance with the *Uniform Plumbing Code*.

1009.3 Interceptor required. If the new occupancy will produce grease or oil-laden wastes, interceptors shall be provided as required in the *Uniform Plumbing Code*.

1009.5 Group I-2. If the occupancy group is changed to Group I-2, the plumbing system shall comply with the applicable requirements of the *Uniform Plumbing Code*.

[Statutory Authority: RCW 19.27.031 and 19.27.074. WSR 23-23-102, § 51-50-481009, filed 11/15/23, effective 3/16/24; WSR 20-21-021, § 51-50-481009, filed 10/9/20, effective 11/9/20.]