

**WAC 480-60-030 Definitions.** The definitions in this section apply throughout this chapter unless the context clearly requires otherwise.

**"Car width"** means twice the distance from the centerline of the car to its extreme outside part.

**"Commission"** means the Washington utilities and transportation commission.

**"Icing platforms"** means structures used in performing the service of icing, precooling, heating, ventilating and servicing of cars used in the handling of commodities requiring those services.

**"Overcrossing"** means any point or place where a highway crosses a railroad by passing above it.

**"Overhead clearance"** means the distance measured along a line which is perpendicular to and joins a horizontal plane passing through the top of the highest rail and a horizontal plane passing through the lowest point of the overhead structure or obstruction.

**"Side clearance"** means the shortest distance from centerline of track to a structure or appurtenances such as downspouts, ladders, or other obstructions at the side of the track.

**"Track clearance"** means the shortest distance between the centerlines of adjacent tracks.

**"Walkways"** means pathways located alongside or in the vicinity of a railroad track, or on a trestle or bridge, that provide an area for a railroad employee to perform duties associated with the track, trestle or bridge.

[Statutory Authority: RCW 81.04.160 and 80.01.040. WSR 00-04-011 (Order No. R-469, Docket No. TR-981101), § 480-60-030, filed 1/21/00, effective 2/21/00; Order R-5, § 480-60-030, filed 6/6/69, effective 10/9/69.]