

WAC 173-491-020 Definitions. The definitions of terms contained in chapter 173-400 WAC are by this reference incorporated into this chapter. Unless a different meaning is clearly required by context, the following words and phrases, as used in this chapter, shall have the following meanings:

(1) "Bottom loading" means the filling of a tank through a line entering the bottom of the tank.

(2) "Bulk gasoline plant" means a gasoline storage and transfer facility that receives more than ninety percent of its annual gasoline throughput by transport tank, and reloads gasoline into transport tanks.

(3) "Canister capture rate" means canister effectiveness times the percent of light duty vehicles that have onboard vapor recovery systems.

(4) "Canister effectiveness" means the percent of refueling vapors recovered by a representative onboard vapor recovery system.

(5) "Centroid" means the geometric center of a gas pump or a bank of gas pumps or, if a station has more than one bank of pumps, the geometric center of each bank of pumps.

(6) "Certified vapor recovery system" means a vapor recovery system which has been certified by the department of ecology. Only Stage II vapor recovery systems with a single coaxial hose can be certified. The department may certify vapor recovery systems certified by the California Air Resources Board as of the effective date of the regulation.

(7) "Eastern Washington county" means the following counties: Adams, Asotin, Benton, Chelan, Columbia, Douglas, Ferry, Franklin, Garfield, Grant, Kittitas, Klickitat, Lincoln, Okanogan, Pend Oreille, Spokane, Stevens, Walla Walla, Whitman, and Yakima.

(8) "Gasoline" means a petroleum distillate which is a liquid at standard conditions and has a true vapor pressure greater than four pounds per square inch absolute at twenty degrees C, and is used as a fuel for internal combustion engines. Also any liquid sold as a vehicle fuel with a true vapor pressure greater than four pounds per square inch absolute at twenty degrees C shall be considered "gasoline" for purpose of this regulation.

(9) "Gasoline dispensing facility" means any site dispensing gasoline into motor vehicle fuel tanks from stationary storage tanks.

(10) "Gasoline loading terminal" means a gasoline transfer facility that receives more than ten percent of its annual gasoline throughput solely or in combination by pipeline, ship or barge, and loads gasoline into transport tanks.

(11) "Leak free" means a liquid leak of less than four drops per minute.

(12) "Modified" means any physical change in, or change in the method of operation of, a gasoline dispensing facility that increases the amount of any air contaminant emitted by such source or that results in the emission of any air contaminant not previously emitted. The term modified shall be construed consistent with the definitions of modification in Section 7411, Title 42, United States Code, and with rules implementing that section. Section 7411 exempts changes in gasoline throughput not resulting directly from a physical change.

(13) "NAAQS" means the National Ambient Air Quality Standard.

(14) "Ozone-contributing county" means a county in which the emissions have contributed to the formation of ozone in any county or area where violations of federal ozone standards have been measured,

and includes: Cowlitz, Island, Kitsap, Lewis, Skagit, Thurston, Wahkiakum, and Whatcom counties.

(15) "Permanent residence" means a single-family or multifamily dwelling, or any other facility designed for use as permanent housing.

(16) "Stage I" means gasoline vapor recovery during all gasoline marketing transfer operations except motor vehicle refueling.

(17) "Stage II" means gasoline vapor recovery during motor vehicle refueling operations from stationary tanks.

(18) "Submerged fill line" means any discharge pipe or nozzle which meets either of the following conditions:

- Where the tank is filled from the top, the end of the discharge pipe or nozzle must be totally submerged when the liquid level is six inches from the bottom of the tank, or;
- Where the tank is filled from the side, the discharge pipe or nozzle must be totally submerged when the liquid level is eighteen inches from the bottom of the tank.

(19) "Submerged loading" means the filling of a tank with a submerged fill line.

(20) "Throughput" means the amount of material passing through a facility.

(21) "Top off" means to attempt to dispense gasoline to a motor vehicle fuel tank after a vapor recovery dispensing nozzle has shut off automatically.

(22) "Transport tank" means a container used for shipping gasoline over roadways.

(23) "True vapor pressure" means the equilibrium partial pressure of a petroleum liquid as determined by methods described in American Petroleum Institute Bulletin 2517, 1980.

(24) "Vapor balance system" means a system consisting of the transport tank, gasoline vapor transfer lines, storage tank, and all tank vents designed to route displaced gasoline vapors from a tank being filled with liquid gasoline.

(25) "Vapor collection system" means a closed system to conduct vapors displaced from a tank being filled into the tank being emptied, a vapor holding tank, or a vapor control system.

(26) "Vapor control system" means a system designed and operated to reduce or limit the emission of gasoline vapors emission into the ambient air.

(27) "Vapor tight" means a leak of less than one hundred percent of the lower explosive limit on a combustible gas detector measured at a distance of one inch from the source or no visible evidence of air entrainment in the sight glasses of liquid delivery hoses.

[Statutory Authority: RCW 70.94.165. WSR 98-01-184 (Order 97-07), § 173-491-020, filed 12/23/97, effective 1/23/98. Statutory Authority: 1996 c 294. WSR 97-04-012 (Order 95-15), § 173-491-020, filed 1/27/97, effective 2/27/97. Statutory Authority: RCW 70.94.331. WSR 93-13-011 (Order 92-47), § 173-491-020, filed 6/7/93, effective 7/8/93; WSR 91-14-101 (Order 90-63), § 173-491-020, filed 7/2/91, effective 8/2/91.]