SENATE BILL 6001

State of Washington58th Legislature2003 Regular SessionBy Senator Benton

Read first time 02/28/2003. Referred to Committee on Highways & Transportation.

1 AN ACT Relating to lawful vehicle combinations; and amending RCW 46.44.037.

3 BE IT ENACTED BY THE LEGISLATURE OF THE STATE OF WASHINGTON:

4 Sec. 1. RCW 46.44.037 and 1991 c 143 s 2 are each amended to read 5 as follows:

6 Notwithstanding the provisions of RCW 46.44.036 and subject to such 7 rules and regulations governing their operation as may be adopted by 8 the state department of transportation, operation of the following 9 combinations is lawful:

(1) A combination consisting of a truck tractor, a semitrailer, and another semitrailer or a full trailer. In this combination a converter gear used to convert a semitrailer into a full trailer shall be considered to be a part of the full trailer and not a separate vehicle. A converter gear being pulled without load and not used to convert a semitrailer into a full trailer may be substituted in lieu of a full trailer or a semitrailer in any lawful combination;

(2) A combination not exceeding seventy-five feet in overall lengthconsisting of four trucks or truck tractors used in driveaway service

1 where three of the vehicles are towed by the fourth in triple
2 saddlemount position;

3 (3) A combination consisting of a truck tractor carrying a freight 4 compartment no longer than eight feet, a semitrailer, and another 5 semitrailer or full trailer that meets the legal length requirement for 6 a truck and trailer combination set forth in RCW 46.44.030<u>;</u>

(4) A combination consisting of a motor vehicle weighing more than 7 four thousand pounds unladen, a travel trailer not exceeding twenty-two 8 feet in length, and a trailer designed for hauling a boat, snowmobiles, 9 or nonhighway vehicles as defined in RCW 46.09.020. The vehicles in 10 combination must not exceed sixty-five feet in length and must have a 11 12 braking capacity in excess of the gross weight of the combination and rear to front progressive braking. The trailers must be connected by 13 hitches designed and attached in such a manner to be capable of towing 14 the gross weight of the trailers in tow. 15

--- END ---