## SENATE BILL 5278

State of Washington 61st Legislature 2009 Regular Session

**By** Senators King, Kohl-Welles, and Shin; by request of Department of Labor & Industries

Read first time 01/19/09. Referred to Committee on Labor, Commerce & Consumer Protection.

AN ACT Relating to making technical changes to boiler and unfired pressure vessel statutes; amending RCW 70.79.060, 70.79.070, 70.79.080, 70.79.090, and 70.79.240; and repealing RCW 70.79.210.

4 BE IT ENACTED BY THE LEGISLATURE OF THE STATE OF WASHINGTON:

5 Sec. 1. RCW 70.79.060 and 1984 c 93 s 1 are each amended to read 6 as follows:

7 (1) Except as provided in subsection (2) of this section, no power 8 boiler, low pressure boiler, or unfired pressure vessel which does not 9 conform to the rules and regulations formulated by the board governing 10 new construction and installation shall be installed and operated in 11 this state after twelve months from the date upon which the first rules and regulations under this chapter pertaining to new construction and 12 13 installation shall have become effective, unless the boiler or unfired 14 pressure vessel is of special design or construction, and is not 15 covered by the rules and regulations, nor is in any way inconsistent 16 with such rules and regulations, in which case ((a special installation and operating permit)) an inspection certificate may at its discretion 17 18 be granted by the board.

1 (2) ((A special permit)) An inspection certificate may also be 2 granted for boilers and pressure vessels manufactured before 1951 which 3 do not comply with the code requirements of the American Society of 4 Mechanical Engineers adopted under this chapter, if the boiler or 5 pressure vessel is operated exclusively for the purposes of public 6 exhibition, and the board finds, upon inspection, that operation of the 7 boiler or pressure vessel for such purposes is not unsafe.

8 Sec. 2. RCW 70.79.070 and 1995 c 41 s 1 are each amended to read 9 as follows:

10 (1) All boilers and unfired pressure vessels which were in use, or 11 installed ready for use in this state prior to the date upon which the 12 first rules and regulations under this chapter pertaining to existing installations became effective, or during the twelve months period 13 immediately thereafter, shall be made to conform to the rules and 14 regulations of the board governing existing installations, and the 15 formulae prescribed therein shall be used in determining the maximum 16 allowable working pressure for such boilers and unfired pressure 17 18 vessels.

19 (2) This chapter shall not be construed as in any way preventing 20 the use or sale of boilers or unfired vessels as referred to in 21 subsection (1) of this section, provided they have been made to conform 22 to the rules and regulations of the board governing existing 23 installations, and provided, further, they have not been found upon 24 inspection to be in an unsafe condition.

(3) ((A special permit)) <u>An inspection certificate</u> may also be granted for miniature hobby boilers that do not comply with the code requirements of the American society of mechanical engineers adopted under this chapter and do not exceed any of the following limits:

29

(a) Sixteen inches inside diameter of the shell;

30

31

(c) Five cubic feet of gross volume of vessel; and

(b) Twenty square feet of total heating surface;

32 (d) One hundred fifty p.s.i.g. maximum allowable working pressure, 33 and if the boiler is to be operated exclusively not for commercial or 34 industrial use and the department of labor and industries finds, upon 35 inspection, that operation of the boiler for such purposes is not 36 unsafe. 1 Sec. 3. RCW 70.79.080 and 2005 c 22 s 1 are each amended to read
2 as follows:

3 This chapter shall not apply to the following boilers, unfired 4 pressure vessels and domestic hot water tanks:

5 (1) Boilers and unfired pressure vessels under federal regulation 6 or operated by any railroad subject to the provisions of the interstate 7 commerce act;

8 (2) Unfired pressure vessels meeting the requirements of the 9 interstate commerce commission for shipment of liquids or gases under 10 pressure;

11 (3) Air tanks located on vehicles operating under the rules of 12 other state authorities and used for carrying passengers, or freight;

(4) Air tanks installed on the right-of-way of railroads and useddirectly in the operation of trains;

(5) Unfired pressure vessels having a volume of five cubic feet orless when not located in places of public assembly;

17 (6) Unfired pressure vessels designed for a pressure not exceeding18 fifteen pounds per square inch gauge;

19 (7) Tanks used in connection with heating water for domestic and/or20 residential purposes;

(8) Boilers and unfired pressure vessels in cities having ordinances which are enforced and which have requirements equal to or higher than those provided for under this chapter, covering the installation, operation, maintenance and inspection of boilers and unfired pressure vessels;

(9) Tanks containing water with no air cushion and no direct source
 of energy that operate at ((a)) <u>ambient</u> temperature ((<del>of one hundred</del>
 thirty degrees Fahrenheit or less));

29 (10) Electric boilers:

30 (a) Having a tank volume of not more than one and one-half cubic 31 feet;

32 (b) Having a maximum allowable working pressure of one hundred 33 pounds per square inch or less, with a pressure relief system to 34 prevent excess pressure; and

35 (c) If constructed after June 10, 1994, constructed to American 36 society of mechanical engineers code, or approved or otherwise 37 certified by a nationally recognized or recognized foreign testing

p. 3

laboratory or construction code, including but not limited to
 Underwriters Laboratories, Edison Testing Laboratory, or Instituto
 Superiore Per La Prevenzione E La Sicurezza Del Lavoro;

4 (11) Electrical switchgear and control apparatus that have no
5 external source of energy to maintain pressure and are located in
6 restricted access areas under the control of an electric utility;

7 (12) Regardless of location, unfired pressure vessels ((and hot 8 water heaters)) less than one and one-half cubic feet (11.25 gallons) in volume ((with a safety valve setting of one hundred fifty pounds per 9 10 square inch qauge (psig) or less,)) or less than six inches in diameter ((and less than five cubic feet (37.5 gallons) in volume with a safety 11 valve set at any pressure, or less than fifteen psig containing 12 13 substances other than steam, lethal substances, or liquids with low flash points)) with no limitation on the length of the vessel or 14 15 <u>pressure;</u>

16 (13) Domestic hot water heaters less than one and one-half cubic 17 feet (11.25 gallons) in volume with a safety valve setting of one 18 hundred fifty pounds per square inch gauge or less.

19 Sec. 4. RCW 70.79.090 and 2005 c 22 s 2 are each amended to read 20 as follows:

The following boilers and unfired pressure vessels shall be exempt from the requirements of RCW 70.79.220 and 70.79.240 through 70.79.330:

(1) Boilers or unfired pressure vessels located on farms and usedsolely for agricultural purposes;

(2) Unfired pressure vessels that are part of fertilizer applicator
 rigs designed and used exclusively for fertilization in the conduct of
 agricultural operations;

(3) Steam boilers used exclusively for heating purposes carrying a pressure of not more than fifteen pounds per square inch gauge and which are located in private residences or in apartment houses of less than six families;

32 (4) Hot water heating boilers carrying a pressure of not more than 33 thirty pounds per square inch and which are located in private 34 residences or in apartment houses of less than six families;

35 (5) Approved pressure vessels (hot water heaters, hot water storage 36 tanks, hot water supply boilers, and hot water heating boilers listed 37 by a nationally recognized testing agency), with approved safety

p. 4

devices including a pressure relief valve, with a nominal water 1 2 containing capacity of one hundred twenty gallons or less having a heat input of two hundred thousand b.t.u.'s per hour or less, ((used for hot 3 4 water supply)) at pressure of one hundred sixty pounds per square inch 5 or less, and at temperatures of two hundred ten degrees Fahrenheit or less: PROVIDED, HOWEVER, That such pressure vessels are not installed 6 7 in schools, child care centers, public and private hospitals, nursing 8 and boarding homes, churches, public buildings owned or leased and 9 maintained by the state or any political subdivision thereof, and 10 assembly halls;

(6) Unfired pressure vessels containing only water under pressure for domestic supply purposes, including those containing air, the compression of which serves only as a cushion or airlift pumping systems, when located in private residences or in apartment houses of less than six families, or in public water systems as defined in RCW 70.119.020;

17

(7) Unfired pressure vessels containing liquified petroleum gases.

18 Sec. 5. RCW 70.79.240 and 1993 c 391 s 1 are each amended to read 19 as follows:

Each boiler and unfired pressure vessel used or proposed to be used within this state, except boilers or unfired pressure vessels exempt in RCW 70.79.080 and 70.79.090, shall be thoroughly inspected as to their construction, installation, condition and operation, as follows:

(1) Power boilers shall be inspected annually both internally and externally while not under pressure, except that the board may provide for longer periods between inspections where the contents, history, or operation of the power boiler or the material of which it is constructed warrant special consideration. Power boilers shall also be inspected annually externally while under pressure if possible;

30 (2) Low pressure heating boilers shall be inspected both internally 31 and externally biennially where construction will permit, except that 32 the board may, in its discretion, provide for longer periods between 33 internal inspections;

(3) Unfired pressure vessels subject to internal corrosion shall be
 inspected both internally and externally biennially where construction
 will permit, except that the board may, in its discretion, provide for
 longer periods between <u>internal</u> inspections;

(4) Unfired pressure vessels not subject to internal corrosion 1 2 shall be inspected externally at intervals set by the board, but internal inspections shall not be required of unfired pressure vessels, 3 the contents of which are known to be noncorrosive to the material of 4 which the shell, head, or fittings are constructed, either from the 5 6 chemical composition of the contents or from evidence that the contents are adequately treated with a corrosion inhibitor, provided that such 7 8 vessels are constructed in accordance with the rules and regulations of 9 the board or in accordance with standards substantially equivalent to the rules and regulations of the board, in effect at the time of 10 11 manufacture.

12 <u>NEW SECTION.</u> Sec. 6. RCW 70.79.210 (Inspectors--Performance bond 13 required) and 1951 c 32 s 35 are each repealed.

--- END ---