

**WAC 173-182-400 Copalis, Flattery Rocks and Quillayute Needles planning standard.** Those covered vessel and facility plan holders that transit or operate within the jurisdictional waters of Washington state east of the Three Nautical Mile Line and north of latitude 47°06'00"N, and south of latitude 48°09'00"N (WGS 1984) must meet the following standards. This area is very rugged, in order to accomplish deployment of resources logistical considerations will need to be planned for. Access to GRP locations may need to be done by helicopter or by land access, plans must identify all of the equipment that could be used to deploy GRPs.

<b>Time (hours)</b>	<b>Boom/Assessment</b>	<b>Minimum Oil Recovery Rate % of WCS volume per 24 hours</b>	<b>Minimum Storage Volume</b>
2	A safety assessment of the spill by work boat with trained crew and appropriate air monitoring, with 1,000 feet of boom could have arrived		
3	Additional 2,000 feet or 4 times the length of the largest vessel of open water boom whichever is less, to be used for containment, protection or recovery could have arrived on scene		
6	Additional 12,000 feet of boom with at least 6,000 feet of open water boom for containment, protection or recovery could have arrived	Capacity to recover the lesser of 3% of worst case spill volume or 12,500 barrels within 24-hour period could have arrived. 100% of the recovery devices must be able to work in open water environments	1 times the EDRC
12	Additional 20,000 feet of boom combination of types appropriate for containment, protection and recovery could have arrived	Capacity to recover the lesser of 10% of worst case spill volume or 36,000 barrels within 24-hour period could have arrived. At least 60% of the skimming capability must be able to work open water environments	1.5 times the EDRC
24	Additional 20,000 feet combination of types appropriate for containment, protection and recovery could have arrived	Capacity to recover the lesser of 14% of worst case spill volume or 48,000 barrels within 24-hour period could have arrived	2 times the EDRC
48	More boom as necessary for containment, recovery or protection	Capacity to recover the lesser of 25% of worst case spill volume or 60,000 barrels within 24-hour period could have arrived	More as necessary to not slow the response

[Statutory Authority: Chapters 88.46, 90.56, and 90.48 RCW. WSR 06-20-035 (Order 00-03), § 173-182-400, filed 9/25/06, effective 10/26/06.]