

**WAC 204-76-99002 Clamp type brake chamber data.**

CLAMP TYPE BRAKE CHAMBER DATA					
Type	Effective Area (Square Inches)	* Outside Diameter	Maximum Stroke With Brakes Adjusted	Maximum Stroke At Which Clamp Type Brakes Must Be Readjusted	Maximum Stroke At Which Long Stroke Clamp Type Brakes Must Be Readjusted
6	6	4 1/2	Should be	1 1/4	
9	9	5 1/4	as short as	1 3/8	
12	12	5 11/16	possible	1 3/8	1 3/4
16	16	6 3/8	without	1 3/4	2
20	20	6 25/32	brakes	1 3/4	2 (2.5" rated stroke) OR 2 1/2 (3" rated stroke)
24	24	7 7/32	dragging	1 3/4	2 (2.5" rated stroke) OR 2 1/2 (3" rated stroke)
30	30	8 3/32		2	2 1/2
36	36	9		2 1/4	

\* Dimensions listed do not include capscrew head projections for bolt clamp projections for clamp type brake chambers.

[Statutory Authority: RCW 46.37.005. WSR 14-03-018, § 204-76-99002, filed 1/7/14, effective 2/7/14; WSR 89-12-019 (Order 89-03-ESR), § 204-76-99002, filed 5/30/89; WSR 88-01-018 (Order 87-04-ESR), § 204-76-99002, filed 12/8/87; WSR 80-10-006 (Order 80-07-01), § 204-76-99002, filed 7/25/80.]