

WAC 296-869-40015 Repairs and adjustments. (1) You must make sure repairs to elevating work platforms are:

- (a) Made by a qualified person; and
- (b) Done according to the manufacturer's recommendations.

(2) You must make sure the elevating work platform, before beginning adjustments or repairs, meets all of the following requirements that apply:

- (a) All controls in the "off" position;
- (b) All operating features secured from inadvertent motion by brakes, blocks, or other means;
- (c) Powerplant stopped;
- (d) Means of starting is rendered inoperative;
- (e) Platform either:
 - (i) Lowered to the full down position, if possible; or
 - (ii) Blocked or cribbed to prevent dropping.
- (f) Hydraulic pressure relieved from all hydraulic circuits before loosening or removing hydraulic components;
- (g) Safety props or latches installed, where applicable;
- (h) Other precautions as specified by the manufacturer; and
- (i) Make sure replacement parts or components are identical or equivalent to the original parts or components.

[Statutory Authority: RCW 49.17.010, 49.17.040, 49.17.050. WSR 15-23-086, § 296-869-40015, filed 11/17/15, effective 12/18/15. Statutory Authority: RCW 49.17.010, 49.17.040, 49.17.050, 49.17.060. WSR 06-19-073, § 296-869-40015, filed 9/19/06, effective 1/1/07.]